

Montage kit 290 ml

Product Description

Montage Kit is a bonding and filling quick drying adhesive based on a high bond strength synthetic rubber/resin mix. For fixing objects of stone, concrete, ceramics, bricks, plastic, wood.

Properties

Solvent based formula-quick drying/high early bond strength.Excellent adhesion/ bond strength-adheres to most common surfaces. Usable in both vertical and horizontal positions. Excellent gap filling properties without shrinkage. Suitable for use where both surfaces are non-porous. Suitable for exterior use. Product not suitable for expanded polystyrene, polypropylene, polyethylene and teflon.

Technical Information

Chemical Base: rubber/resin mixture
 Appearance: paste
 Specific gravity: 1,24 ±0,03 g/cm³
 Tack free time: < 30 second (25 °C and 50% R.H)
 Tensile Strength: 5 N/mm²
 Volume loss: 27%

Application Details

Application Temperature: +5 °C to 35 °C
 Temperature Resistance: -40 °C to 90 °C
 Application surface must be clean, dry and free of dust, oil and grease.

Shelf Life

Store the product in a cool and dry place.
 The shelf life is 12 months at temperatures between +5 °C and +25 °C.

Caution

Avoid contact with skin and eyes. Use gloves before application. Keep out of freezing, direct sunlight and temperatures above 50 °C. Apply in well-ventilated areas. Do not breathe vapor. Do not smoke.

Health and Safety

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing, physical, ecological, and toxicological and other safety related data.




Code

Barcode

MNK

8606007997576

Logistics data

Barcode	8606007997576			Code
Cartridge length	23,3			MNK
Cartridge width	4,9			
Cartridge diameter	4,9			
Packaging	Dimensions	Number of boxes	Number of cartridge	Gross weight (Kgs)
Commercial packaging	25.2.x25.2x25	1	25	10,5
Transpot packing	25.2.x25.2x25	1	25	10,5
Pallet for storage	1200x800x2200	90	2250	975
Pallet for transport	1200x800x2200	90	2250	975